

3G PLUG & PLAY VEHICLE GPS TRACKER

Trakpro
FLEET MANAGEMENT



Plug & play

This tracker with OBD II connector is aimed to achieve fast and easy installation.

Disconnect alert

An alert will be generated when the device is removed from the OBD connector.

Regular maintenance

Ensure the safety, reliability, drivability, comfort and longevity of a car.

Multiple alerts & reports

Support speeding/SOS/geo-fence alert, ACC ON & OFF/mileage/cornering report etc.

APPLICATION



Private Car



Taxi



Truck

SPECIFICATIONS

| ITEM | SPECIFICATIONS |
|-----------------------|--|
| Dimension | 69.8 mm x 51.8 mm x 31.8 mm |
| Weight | 60g |
| Power supply | DC 12 V/24V 1A |
| Backup battery | 170 mAh/3.7 V (24 hours in power-saving mode; 1.5 hours in normal mode) |
| Power consumption | Current in standby mode: 100 mA |
| Operating temperature | -20°C to 55°C |
| Operating humidity | 5% to 95% |
| LED indicator | 2 indicators showing WCDMA, GSM and GPS status |
| Button/Switch | 1 SOS button 1 power button |
| Microphone | 8 MB buffer |
| Memory | 8 MB buffer |
| Sensor | 3-axis accelerometer |
| Frequency band | TC68SG: UMTS/HSDPA: 800/850/900/1900/2100 MHz GSM/GPRS: 850/900/1800/1900 MHz TC68SG_A: UMTS/HSDPA: 850/1900 MHz TC68SG_E: UMTS/HSDPA: 900/2100 MHz GSM/GPRS: 900/1800 MHz |
| GPS sensitivity | -161 dB |
| Positioning accuracy | 2.5m |
| I/O port | 1 USB port |
| I/O port | 1 USB port |



ACCESSORIES

TC68SG Tracker
Backup battery (170
mAh/3.7 V)
CD download card



OPTIONAL ACCESSORIES

OBD extension cord
Velcro
USB cable